

XG836EL

XG839FL



◆ High-end first-class core configuration

Cummins engine in accordance with stage II/III, excellent power.

Isuzu engine in accordance with stage II/III, fuel-saving and energy-saving.

International brand main pump and main valve

World brand hydraulic components to ensure high reliability of hydraulic system

◆ Higher reliability and durability

Sturdy high-strength body

Reinforced movable arm, bucket bar and bucket structural parts

More coordinated comfort

◆ Highly rigid new cab, quiet and comfortable

Color LCD monitor for easy monitoring and maintenance

Multiple operation modes available

Performance Parameter and Dimensions

MODEL	XG836EL	XG839FL
Operating Weight(T)	35	37.5
Bucket capacity(m3)	1.6-1.8	1.6-1.9
Engine model	CUMMINS 6LTAA8.9	ISUZU 6HK1X
Power(kw/r/min)	241/2000	212/2000
Volume of fuel tank (L)	595	595
Travel speed (km/h)	5.2/3.3	5.2/3.3
Swing speed(r/min)	10.6	8.5
Gradeability(%)	70	70
Bucket digging force(KN)ISO	227	256
Arm length(mm)	3185	2900
Boom (m)	6470	6470
Ground pressure(KPa)	69.4	70.8
Hydraulic oil tank capacity(L)	310	310